

**PAT-NO:** JP410219225A  
**DOCUMENT-IDENTIFIER:** JP 10219225 A  
**TITLE:** ADHESIVE COMPOSITION  
**PUBN-DATE:** August 18, 1998

**INVENTOR-INFORMATION:**

NAME	COUNTRY
SAKUYAMA, HIROSHI	
KOU, REISHIYUU	
HAYASHI, MASAZOE	

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
NIPPON MEKTRON LTD	N/A

**APPL-NO:** JP09035735  
**APPL-DATE:** February 5, 1997

**INT-CL (IPC):** C09J179/08 , C09J163/00 , H05K003/38 ,  
C08G059/50

**ABSTRACT:**

**PROBLEM TO BE SOLVED:** To obtain the subject composition capable of improving adhesiveness under a room

temperature condition, useful for bonding flexible printed board, by using a siloxane polyimide soluble in an organic solvent of general purpose as an adhesive component.

SOLUTION: This composition comprises (A) a siloxane polyimide composed of a copolymer of (i) a diaminopolysiloxane-alicyclic diamine mixture and (ii) an aromatic tetracarboxylic acid dianhydride, (B) an epoxy resin, (C) a diamine- based curing agent, (D) a fluorine surfactant and (E) an organic solvent. For example, a reaction product of a compound of the formula (R is a 2-6C bifunctional hydrocarbon; R1 to R4 are each a 1-5C alkyl or phenyl; (n) is 0-30), etc., and 1,3-bis(aminomethyl)cyclohexane, etc., is preferably used as the component (i).

COPYRIGHT: (C)1998,JPO